



PERFECT
ENGINEERING
SERVICES

Manual Butterfly Valve



Perfect Engineering Services offers rubber lined Butterfly Valves for HVAC and Utilities. These valves are truly Fit and Forget Valves which requires minimum maintenance.

The body lines which also functions as the soft seat, comes in an integrally moulded version and offers bi-directional sealing against vacuum upto the pressure of PN10 / Pn16

Size Range - 1.5" to 40"

TECHNICAL SPECIFICATION

Body	I.C./CI(IS210 Gr FG200) WCB/S.S. 304/S.S. 316
Disc	CF8/CF8M,CF3M/S.G. Iron/Teflon Quoted/Power Coated Nylon Coated /Rubber Line
Seat	EPDM/Nitrile/Haypion/Viton/Moulded or replaceable muffler type
Shaft	AISI 410/ CF8/CF8M/CF3M
Valve Type	Centric Disc Butterfly Valve with a single piece rubber lined body
Body Type	Sandwich between flanges
Seat Type	Integrally moulded with the body
End Connection	Wafer Sandwiched (Lug Type on Request)
Pressure Rating	PN 10/PN 16 (On Request)
Operating Temp. Range	-25°C to 130°C (depending on MOC)
Seat Leakage	Tight Shut Off
Operation	Hand lever for sizes from 40 MM to 350 MM
	Worm gear boxes from 40MM to 1000MM

*Owing to continuous improvements, product specifications and dimensions are subject to change

HEAD OFFICE:

PERFECT ENGINEERING SERVICES

C-601, Badhwar Apartments, Plot No.3, Sector-6, Dwarka, New Delhi-110075

Ph: 011 - 28034280/81 | +91-9891016735 / +91-9350216735 | +91-9999991337 | +91-9811557391

vksood@perfect.org.in | sales@perfect.org.in | info@perfect.org.in | solutions@perfect.org.in

www.perfectengineeringservices.co.in