



PERFECT ENGINEERING SERVICES

Y-Type Flush Bottom Valve



Features / Benefit	Type : “ Y “ Type Rising Disc type, Disc Open into Tank Dead Space (Cavity and Crevice Free) Easily Flushable, Swivel disc Replaceable PTFE seats or Integrated Metal Seat Full Bore, Reduce Bore
ANSI Class / Rating	ASA 150#
Design Standard	Manufacturer
Testing Standard	As per API-598.
Size	40mmX40mm to 150mmX150mm
Materials	Single Piece Investment casted Body Body : CF8, CF8M, CF3M, WCB, LCB etc Seat : PTFE or Metal to Metal
Ends	Flange End 150#
Operation	Manual hand Wheel
Application	Y Type Flush bottom valve are used to discharge Liquids / Slurry from the bottom of Reactors, Receivers & huge Tanks.

Ball-Type Flush Bottom Valve

Features / Benefit	Type : “Ball” Type Reduce Bore, Replaceable PTFE seats Easily Flushable, Operated at 45 Deg, Blow Out Proof Stem, Low Torque Reduced dead space Area with minimum space between the ball and the bottom of Tank
ANSI Class / Rating	ASA 150#
Design Standard	Manufacturer
Testing Standard	As per BS5146/API-598
Size	40mmX25mm to 150mmX150mm
Materials	Single Piece Investment casted Body Body : CF8, CF8M, CF3M, WCB, LCB etc Seat : PTFE, (GFT/PEEK on request)
Ends	Flange End 150# (300# on request)
Operation	Manual hand wheel
Application	Ball type flush bottom ball valve is used to drain/discharge liquids from the bottom of vessel, reactors & tanks. Especially suitable where space below vessel, tank or reactor is insufficient.
User Industries	Chemical, Pharmaceutical, Hydrocarbon, Paints etc



*Owing to continuous improvements, product specifications and dimensions are subject to change

HEAD OFFICE:

PERFECT ENGINEERING SERVICES

C-601, Badhwar Apartments, Plot No.3, Sector-6, Dwarka, New Delhi-110075

Ph: 011 - 28034280/81 | +91-9891016735 / +91-9350216735 | +91-9999991337 | +91-9811557391

vksood@perfect.org.in | sales@perfect.org.in | info@perfect.org.in | solutions@perfect.org.in

www.perfectengineeringservices.co.in