



PERFECT ENGINEERING SERVICES

Safety Valves

Thermal Relief Valve

Extensively used in large Pipe Lines, Small Reactors / Vessels to release Pressure generated by thermal expansion.

Size	: 15 x 25NB, 20 x 25NB & 25 X 40NB 40 X 50NB & 50 X 50NB
Rating	: Suitable for working pressure upto 200 bar
Material	: Forged Steel & Investment Cast Stainless Steel
End Connection	: Screwed & Socket Weld



Safety Relief Valve

Open Bonnet, Conventional Design, Open Cap with Lever. Designed as per API 526/ API 520 and also as per ASME Section VIII. Ideally suitable for Steam Services. Set pressure varies from 0.7 Kg/cm²

More than 15000 valves installed on boilers across the country.

Size	: 25 x 50NB to 250 x 350NB
Rating	: BS 10 Table H, Class 150 to Class 900
Orifice Size	: G(20.0 mm) to V(181.0 mm)
Material	: Carbon Steel, Stainless Steel & Alloy Steel
End Connection	: Flanged



*Owing to continuous improvements, product specifications and dimensions are subject to change

HEAD OFFICE:

PERFECT ENGINEERING SERVICES

C-601, Badhwar Apartments, Plot No.3, Sector-6, Dwarka, New Delhi-110075

Ph: 011 - 28034280/81 | +91-9891016735 / +91-9350216735 | +91-9999991337 | +91-9811557391

vksood@perfect.org.in | sales@perfect.org.in | info@perfect.org.in | solutions@perfect.org.in

www.perfectengineeringservices.co.in