

Parallel Slide Blow Down Valve

Introducing Pesflow's Cast Steel Parallel Slide Blow Down Valve, Rack & Pinion operated with renewable stainless steel trim, Flanged ends, Flanges as per ASME B16.5 . Maximum service temp. 400°C. Each Valve is supplied with operating key.

Testing & Certification

Class 300 / Table J / Table H	
Body Test Pressure	84.36 kg/cm ² (1200 Psig) Hyd.
Seat Test Pressure	42.18 kg/cm ² (600 Psig) Hyd.



Materials

P.No	Components	Material	Material Code
1	Body, Bonnet, Stuffing Box, Gland	Cast Carbon Steel / Bronze Grade B	CS / BRONZE
2	Rack & Pinion	Stainless Steel / Bronze Grade B	SS410 / SS304 / BRONZE
3	Body Seat Rings & Disc	Stainless Steel	SS410
4	Spring	Stainless Steel / Spring Steel	SS304 / SP5
5	Gasket	Non Asbestos / Compressed Asbestos	NASB / CAF
6	Gland Packing	Pure Graphite / Graphite Asbestos / Non Asbestos	GR / GASB / NASB
7	Operating Key	Mild Steel	MS

Address

Head Office:

Perfect Engineering Services

C-601, Badhwar Apartments, Plot No.3, Sector-6, Dwarka, New Delhi-110075

Ph: +91-9891016735 | +91-9350216735 | +91-9999991337 | +91-9811557391

vksood@perfect.org.in | solutions@perfect.org.in

www.perfectengineeringservices.co.in

